



24W LED BULKHEAD CEILING LIGHT



SKU Code:
T750 - 6000k
T751 - 4000k

85lm/w
LUMENS

24W
WATTS

IP65

This fitting is a 24W LED bulkhead light fitting ideal for outdoor wall lighting. It has an IP65 rating (it is waterproof) and offers a 6000k/4000K light. With a 110mm projection and approx. 280mm diameter, this bulkhead has a poly carbonate base in white, a gloss white trim ring, and an opal diffuser.

Features

- This range of LED bulkheads are robust and versatile with an IP65 rating which protects from dust and jets of water.
- They are ideal for hospitals, nursing homes, schools, and any other commercial or domestic environments, both indoors and outdoors as needed.
- Mains voltage: 240V supply 50/60Hz.
- 24W SMD LED lamp, 6000k/4000K
- Lumens: 2040lm
- Dimensions: 280mm diameter.
- Finish: white ring and opal poly carbonate diffuser.
- IP rating: IP65 rated bulkhead.
- Mounting: ceiling or wall mounted.
- Working temperature: -20 deg to +60 deg.
- Lunar bulkhead for both exterior and interior lighting.

Specifications

| | |
|-------------------------------|--------------------------------|
| Wattage | 24W |
| Housing Material | ABS |
| Housing Colour | White |
| CCT | 6000k(T750), 4000k(T751) |
| Input Voltage | 170V-250V, 50/60 Hz |
| Product Measurement | Ø280*63mm |
| RA | 80 |
| PF | >0.5 |
| Dimmable | No |
| Power Supply | Internal CE standard IC Driver |
| Lumens Per Watt | 85 |
| Luminous flux | 2040 lm |
| Beam | 180 |
| IP Rating | IP65 |
| IK Rating | IK10 |
| Suitable temperature | -20~+45 |
| Switching cycles | ≥15000 |
| Starting time (Seconds) | <15 |
| Energy efficiency class | A+ |
| Accessories | Surface Mounting Kit Included |
| Quick Connector | Included |
| Colour Box Dimension | 290*75*390mm |
| Product Weight with Colourbox | 0.955 Kgs |
| Pcs per Master Carton | 5 pcs |
| Master Carton Dimension | 39.5X30.5X31CM |
| Master Carton Weight | 6.5Kgs |
| Lifetime | 30000 hours |